

様式5 添付 (光学データの参考例)

屋内照明器具特性

製品品番と合わせて公共施設用形式を併記のこと

例

LSS9-4-65

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束 4 % 下方光束 96 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30
保守率	良 0.83 中 0.81 否 0.77	室高数	照度率 (X0.01)																ZCM			
下方投影面積 等価発光面積	cm^2 cm^2	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25			
取付高さ	器具間隔最大限		0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	35		
	横方向 (A)	縦方向 (B)	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41		
1.5m	2	2.19m	1.25	77	67	59	53	75	65	58	52	71	63	57	52	68	61	55	51	48		
2	2.64	2.76	1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	63	60	56	53		
2.5	3.29	3.35	2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60		
3	3.93	3.96	2.5	90	83	77	72	88	82	76	72	84	79	74	70	81	76	72	69	65		
			3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69		
			4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74		
			5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	78		
			7.0	101	97	94	92	99	96	93	90	95	93	90	88	92	89	88	86	82		
			10.0	102	100	98	96	101	98	96	94	97	95	93	92	94	92	91	89	85		

